REV. B - SIC - 8/20/2019 - REMOVED NOTE 1; UPDATED ANNOTATIONS REV. C - SIC - 10/6/2020 - ADDED TOP RAIL REDUCTION FEATURE TO CHANGE TOP RAIL TO 2", WAS 3"; REPLACED RIGHT VIEW WITH SECTION A-A; ADDED DETAIL B GALV. STEEL TOP RAILS 45.0° 48" 18" 1" Ø1/2"-13 UNC LIFTING INSERT (4X) SOLID BOTTOM STEEL REINFORCED CONCRETE 31" - 20" — **DETAIL B** ϕ 1/4" INSERT FOR 3" CABLE CLIP (1X) **SCALE 1 : 12** 36" 44" **SECTION A-A** ≻A AASHTO H-20 RATED - 32,000 LB. SINGLE AXLE LOAD DESCRIPTION: DRAWN BY: ROSS LAGER **HEAVY TRAFFIC CHANNEL** 1/18/2019 **CREATED DATE: REVISION LEVEL:** C DIMENSIONS ARE IN INCHES CONTACT INFORMATION: TOLERANCES: SAVED BY: scallahan EMAIL: INFO@CONCASTINC.COM 10/6/2020 SAVED DATE: SHEET 1 OF 1 FRACTIONAL: ± 1/8" PHONE: (507) 732-4095 1010 NORTH STAR DRIVE ANGULAR: ± 2° FAX: (507) 732-4094 P.O. BOX 69 WEIGHT: MATERIAL: PART NUMBER: ZUMBROTA, MN 55992-0069

802036HT3 45L

CONCRETE

1539 LBS.