



REV. B - SIC - 6/24/2020 - UPDATED ANNOTATIONS; UPDATED WEIGHT RATING TO MAX H-40; WAS H-20; ADDED SOIL BEARING PRESSURES









MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 3,000 PSF; H-20: 3,000 PSF

DRAWN BY: ROBIN FLINT

CREATED DATE: 3/21/2011 REVISION LEVEL: B
SAVED DATE: 6/24/2020 SAVED BY: scallahan

WEIGHT:

895 LBS.

MATERIAL: CONCRETE



1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069

DESCRIPTION:

HT CHANNEL; 22.5 DEG. ANGLE

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL: ± 1/8"
ANGULAR: ± 2°

CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

8030HT3 22.5R