

GALV. STEEL TOP RAILS STEEL REINFORCED CONCRETE  $\emptyset$  1/4" INSERT FOR CABLE CLIP (2X) 34 1/2"

**NOTE 1:** FOR NON-STANDARD LENGTHS THE CHANNEL WILL BE SOLID BOTTOM ANDDESIGNATED WITH ITS CORRESPONDING LENGTH MEASUREMENT. IE: 804024HT 32"

MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 3,000 PSF; H-20: 3,000 PSF

804024HTSB

PART NUMBER:

DRAWN BY: ROBIN FLINT				
CREATED DATE: 4/4	4/2011	REVISION LEVEL: B		
SAVED DATE: 8/13	3/2020	SAVED BY: scallahan		
WEIGHT:	MATERIAL:			
1970 LBS.	CC	NCRETE		



DESCRIPTION: HEAVY TRAFFIC CHANNEL			
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	SHEET 1 OF	