

**NOTE 1:** FOR NON-STANDARD LENGTHS THE CHANNEL WILL BE SOLID BOTTOM AND DESIGNATED WITH ITS CORRESPONDING LENGTH MEASUREMENT. IE: HT6F3012 32"

MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 3,000 PSF; H-20: 3,000 PSF

DRAWN BI. RODIN FLIMI				
CREATED DATE:	4/1/2011	REVISION LEVEL: 0		
SAVED DATE:	8/24/2020	SAVED BY: scallahan		
WEIGHT: MATER		RIAL:		
2317 L	BS. CO	ONCRETE		

DRAWN RV. DORINI FIINIT



HEAVY TRAFFIC CHANNEL			
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	SHEET 1 OF 1	

PART NUMBER:

DESCRIPTION:

HT6F3012