


REV. B - SIC - 7/13/2020 - UPDATED WEIGHT RATING NOTE; ADDED SOIL BEARING PRESSURES







NOTE 1: FOR NON-STANDARD LENGTHS THE CHANNEL WILL BE SOLID BOTTOM AND DESIGNATED WITH ITS CORRESPONDING LENGTH MEASUREMENT. IE: HTF1024 32"

MAX AASHTO H-40 RATED - 64,000 LB. SINGLE AXLE LOAD DEPENDENT ON TRENCH COVER RATING
MINIMUM ALLOWABLE SOIL BEARING PRESSURE – H-40: 5,500 PSF; H-20: 3,000 PSF

DRAWN BY: ROBIN FLINT

4/4/2011 **CREATED DATE:** REVISION LEVEL: B SAVED BY: scallahan 7/13/2020 **SAVED DATE: MATERIAL:**

24"

WEIGHT:

CONCRETE 1205 LBS.



ZUMBROTA, MN 55992-0069

HEAVY TRAFFIC CHANNEL

DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°

CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

DESCRIPTION:

HTF1024 48"