



**NOTE 1:** STANDARD DEPTH OF 40" IS SHOWN. OTHER DEPTHS ARE AVAILABLE UPON REQUEST.

**NOTE 2:** FOR PVC SIZES SMALLER THAN 4", USE CONCAST RC41 (REDUCING COUPLER).

**NOTE 3:** FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-1.5) OR SURELOCK BOLTS (P/N: SL.38-1.25) CAN BE ADDED

AASHTO H-20 RATED – 32,000 LB. SINGLE AXLE LOAD

DRAWN BY: <b>JESSE GUTTING</b>	
CREATED DATE: <b>4/20/2020</b>	REVISION LEVEL: <b>0</b>
SAVED DATE: <b>4/21/2020</b>	SAVED BY: <b>jgutting</b>
WEIGHT: <b>2228 LBS.</b>	MATERIAL: <b>NOTED</b>

  
 1010 NORTH STAR DRIVE  
 P.O. BOX 69  
 ZUMBROTA, MN 55992-0069

DESCRIPTION: <b>CONCRETE PULL BOX W/ SPA COVER</b>	
DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: $\pm 1/8\text{'}$ ANGULAR: $\pm 2^\circ$	CONTACT INFORMATION: EMAIL: <a href="mailto:INFO@CONCASTINC.COM">INFO@CONCASTINC.COM</a> PHONE: (507) 732-4095 FAX: (507) 732-4094
PART NUMBER: <b>PB4-32-44-40-SPA</b>	
SHEET 1 OF 1	