


NOTE 1: STANDARD DEPTH OF 48" IS SHOWN. OTHER DEPTHS ARE AVAILABLE UPON REQUEST.

NOTE 2: FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-1.5) OR SURELOCK BOLTS (P/N: SL.38-1.25) CAN BE ADDED

AASHTO H-20 RATED – 32,000 LB. SINGLE AXLE LOAD

| | | | | | |
|--------------------------------|---------------------------|---|--|--|--------------|
| DRAWN BY: JESSE GUTTING | |  1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069 | DESCRIPTION: CONCRETE PULL BOX W/ GALV. STEEL COVER | | |
| CREATED DATE: 4/8/2020 | REVISION LEVEL: A | | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2° | CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094 | SHEET 1 OF 1 |
| SAVED DATE: 8/2/2021 | SAVED BY: jgutting | | PART NUMBER: PBKO1-72-96-48-RSG | | |
| WEIGHT: 9164 LBS. | MATERIAL: NOTED | | | | |