REV. B - SIC - 7/19/2019 - UPDATED ANNOTATIONS, DIMENSIONS, AND VIEWS REV. C - SIC - 7/19/2019 - UPDATED TITLEBLOCK; UPDATED WEIGHT RATING TO H-20, WAS PEDESTRIAN RATED; UPDATED OVERALL WEIGHT TO 16,821 LBS, WAS 16,878 LBS; UPDATED COVER NOTE AND WEIGHT 1/2-13 UNC INSERT FOR LIFTING (4X) 3/8-16 UNC X 1.5" LG HEX HD BOLT 120" P/N: HHB.38-1.5 ALUM. ID PLATE "CONCAST" "C" P/N: LTR-ID H-20 HEAVY TRAFFIC RATED REINFORCED CONCRETE COVER W/ SPRING ASSISTED RSG COVER "D" **"B"** 72" 84" ~4504 LBS. P/N: 84-120-SA CONCRETE PULL BOX ~12317 LBS. P/N: PBKO1-84-120-54 "A" A-ANCHORS FOR LIFTING (4X) 5" DEEP KNOCKOUTS CAST INTO ALL 4 SIDES 9" X 9" DRAIN HOLE \emptyset 1/2"-13 UNC INSERTS (12X) FOR LIFTING AND BOLT DOWN 1/2-13 UNC INSERT (4X) FOR-PULLING EYES. LOCATED ON BOX INTERIOR (1X PER SIDE) 19" TYP 15" TYP 60'' 24" ID TYP 21" \rightarrow 42" ID TYP SIDE "A" (HLR) SIDE "B" (HLR) SIDE "C" SIDE "D" (HLR)

NOTE 1: FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-1.5) OR SURELOCK BOLTS (P/N: SL.38-1.25) CAN BE ADDED

AASHTO H-20 RATED – 32,000 LB. SINGLE AXLE LOAD

DRAWN BY: ROBIN FLINT			
CREATED DATE:	6/24	1/2011	REVISION LEVEL: C
SAVED DATE:	8/17	7/2021	SAVED BY: scallahan
WEIGHT:		MATERIAL:	
16821 LBS. NOTED			



DESCRIPTION: PULL BOX WITH SPRING-ASSIST RSG COVER

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL: ± 1/8"
ANGULAR: ± 2°

CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

PBKO1-84-120-54-SA