



NOTE 1: THIS STEP MEETS OR EXCEEDS ASTM C 478 AND OSHA STANDARDS WHEN PROPERLY INSTALLED.
NOTE 2: MINIMUM CONCRETE STRENGTH MUST BE 3,000 PSI.
NOTE 3: MODEL DESIGN IS AN APPROXIMATION AND VARIES FROM ACTUAL PRODUCT

PREFORMED HOLE REQUIREMENTS:
(2) Ø 1.1 HOLES TAPERING TO Ø 7/8" TO 3-1/2" DEPTH
HOLES MUST BE PARALLEL

DRILLED HOLE REQUIREMENTS:
(2) Ø 1" HOLES DRILLED TO 3-3/4" MIN DEPTH
HOLES MUST BE PARALLEL
USE A 1" MASONRY DRILL BIT

DRAWN BY: ROBIN FLINT			 CONCAST 1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069	DESCRIPTION: POLYPROPYLENE STEP			
CREATED DATE:	4/21/2009	REVISION LEVEL:		A	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2°	CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094	SHEET 1 OF 1
SAVED DATE:	6/6/2024	SAVED BY:		scallahan			
WEIGHT:	2.3 LBS.	MATERIAL:		NOTED	PART NUMBER: STP-1		