



NOTE 1: FOR ADDED SECURITY, SURELOCK BOLTS (P/N: SL.38-2.5) CAN BE ADDED

AASHTO H-20 RATED – 32,000 LB. SINGLE AXLE LOAD

|                                 |                                     |
|---------------------------------|-------------------------------------|
| DRAWN BY: <b>JESSE GUTTING</b>  |                                     |
| CREATED DATE: <b>12/15/2015</b> | REVISION LEVEL: <b>0</b>            |
| SAVED DATE: <b>3/11/2022</b>    | SAVED BY: <b>jgutting</b>           |
| WEIGHT: <b>428 LBS.</b>         | MATERIAL: <b>WELDED GALV. STEEL</b> |

**CONCAST**  
 1010 NORTH STAR DRIVE  
 P.O. BOX 69  
 ZUMBROTA, MN 55992-0069

|  |  |              |
|--|--|--------------|
| DESCRIPTION:<br><b>SG SPRING-ASSISTED COVER W/PADLOCK</b>                      |  | SHEET 1 OF 2 |
| DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL: ± 1/8"<br>ANGULAR: ± 2° | CONTACT INFORMATION:<br>EMAIL: INFO@CONCASTINC.COM<br>PHONE: (507) 732-4095<br>FAX: (507) 732-4094 |              |
| PART NUMBER:<br><b>44-56-SPA-LK</b>  |  |              |