



NOTE 1: FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-2.5) OR SURELOCK BOLTS (P/N: SL.38-2.5) CAN BE ADDED

AASHTO H-20 RATED – 32,000 LB. SINGLE AXLE LOAD

|                                |                                 |
|--------------------------------|---------------------------------|
| DRAWN BY: <b>JESSE GUTTING</b> |                                 |
| CREATED DATE: <b>9/2/2020</b>  | REVISION LEVEL: <b>C</b>        |
| SAVED DATE: <b>3/9/2022</b>    | SAVED BY: <b>jgutting</b>       |
| WEIGHT:<br><b>956 LBS.</b>     | MATERIAL:<br><b>GALV. STEEL</b> |



1010 NORTH STAR DRIVE  
P.O. BOX 69  
ZUMBROTA, MN 55992-0069

|  |   |              |
|--|---|--------------|
| DESCRIPTION:<br><b>SG SPRING ASSISTED COVER &amp; FRAME</b>                    |   | SHEET 1 OF 2 |
| DIMENSIONS ARE IN INCHES<br>TOLERANCES:<br>FRACTIONAL: ± 1/8"<br>ANGULAR: ± 2° | CONTACT INFORMATION:<br>EMAIL: <a href="mailto:INFO@CONCASTINC.COM">INFO@CONCASTINC.COM</a><br>PHONE: (507) 732-4095<br>FAX: (507) 732-4094 |              |
| PART NUMBER:<br><b>72-72-SPA</b>   |   |              |