



NOTE 1: FOR ADDED SECURITY, PENTA HEAD (P/N: PTA.38-1.5) OR SURELOCK BOLTS (P/N: SL.38-1.5) CAN BE ADDED
NOTE 2: FOR PVC SIZES SMALLER THAN 4", USE CONCAST RC41 (REDUCING COUPLER).

AASHTO H-20 RATED - 32,000 LB. SINGLE AXLE LOAD

| | | | | |
|----------------------------------|--------------------------|---|--|--|
| DRAWN BY: SAMUEL CALLAHAN | |  1010 NORTH STAR DRIVE P.O. BOX 69 ZUMBROTA, MN 55992-0069 | DESCRIPTION: | |
| DATE: 5/30/2019 | REVISION LEVEL: 0 | | CONCRETE PULL BOX W/SPA COVER | |
| WEIGHT: 4052 LBS. | MATERIAL: NOTED | | DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ± 1/8" ANGULAR: ± 2° | CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094 |
| | | | PART NUMBER: PB4-44-56-52-SPA | |