

NOTE 1: USED FOR COSMETIC REPAIRS - 9" X 12" PATCH

**NOTE 2:** KIT INCLUDES PATCH & INSTRUCTIONS

NOTE 3: HARDENS UNDER UV LIGHT WITHIN 10 TO 60 MINUTES

NOTE 4: PATCH CAN BE DRILLED, SANDED OR PAINTED AFTER FULLY CURED.

NOTE 5: CONCAST RECOMMENDS CLEANING CRACKED SURFACE WITH ACETONE PRIOR TO PATCH APPLICATION FOR BETTER ADHESION

**NOTE 6:** SHELF LIFE IS 1.5 YEARS

NOTE 7: SEE WEB FOR TECHNICAL SPECS IN BROCHURE. www.concastinc.com/product\_specs/Catalogs/PatchKwik\_Brochure\_web.pdf

## DRAWN BY: ROBIN FLINT

CREATED DATE: 7/1/2009 REVISION LEVEL: A
SAVED DATE: 8/12/2020 SAVED BY: jgutting

WEIGHT: MATERIAL:

.7 LBS.



## DESCRIPTION:

## SELF ADHESIVE REPAIR PATCH

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL: ± 1/8"
ANGULAR: ± 2°

CONTACT INFORMATION: EMAIL: INFO@CONCASTINC.COM PHONE: (507) 732-4095 FAX: (507) 732-4094

SHEET 1 OF 1

PART NUMBER:

PK-912